

## ALUMIINIUM KORPUSEGA T3A INSTALLATSIOONITABEL

TÜÜP	Laagrid		KK	H	Jalgade mõõdud				Võll							Korpuse mõõdud							
	Esimene	Tagumine			A	B	C	K	D	E	F	G	SS	XX	ZZ	AB	AD	HD	AC	L	TBS	TBW	TBH
T3A 80	6204		1-M20x1.5	80	125	100	50	9	19	40	6,0	15,5	M6	16	21	160	214	134	157	277	26,5	109	109
T3A 90S/L	6205		1-M20x1.5	90	140	100/125	56	10	24	50	8	20	M8	19	25	176	235	145	177	313/338	28,5	109	109
T3A 100	6206		2-M20x1.5	100	160	140	63	12	28	60	8	24	M10	22	30	200	260	160	199	376	32	118	118
T3A 112	6306	6206	2-M25x1.5	112	190	140	70	12	28	70	8	24	M10	22	30	224	283	171	220	397	33	118	118
T3A 132S/M	6308	6208	2-M25x1.5	132	216	140/178	89	12	38	80	10	33	M12	28	37	260	323	191	261	460/498	36,5	118	118
T3A 160M/L	6309	6209	2-M32x1.5	160	254	210/254	108	15	42	110	12	33	37	36	45	314	391	231	314	616/660	64,0	148	148

TÜÜP	B5						B14						B5R						B14B					
	N	M	P	S	T	R	N	M	P	S	T	R	N	M	P	T	S	R	N	M	P	T	S	R
T3A 80	130	165	200	12	3,5	0	80	100	120	M6	3	0	110	130	160	3,5	10	0	110	130	160	3,5	M8	0
T3A 90S/L	130	165	200	12	3,5	0	95	115	140	M8	3	0	110	130	160	3,5	10	0	110	130	160	3,5	M8	0
T3A 100	180	215	250	15	4	0	110	130	160	M8	3,5	0	130	165	200	3,5	12	0	130	165	200	3,5	M10	0
T3A 112	180	215	250	15	4	0	110	130	160	M8	3,5	0	130	165	200	3,5	12	0	130	165	200	3,5	M10	0
T3A 132S/M	230	265	300	15	4	0	130	165	200	M10	3,5	0	180	215	250	4	15	0	180	215	250	4	M12	0
T3A 160M/L	250	300	350	19	5	0	180	215	250	M12	4,0	0												

