

MALM KORPUSEGA T3C INSTALLATSIOONITABEL

TÜÜP		Laagrid		H	Jalgade mõõdud				Võlli mõõdud				Korpuse mõõdud				B5				
		Esimene	Tagumine		A	B	C	K	D	E	F	G	AB	HD	AC	L	N	M	P	S	T
T3C 112		6306		112	190	140	70	12	28	60	8	24	230	179	220	405	180	215	250	15	4
T3C 132S/M		6308		132	216	140/178	89	12	38	80	10	33	255	200	259	467/505	230	265	300	15	4
T3C 160M/L		6309		160	254	210/254	108	15	42	110	12	37	314	242	313	605/650	250	300	350	19	5
T3C 180M/L		6311		180	279	241/279	121	15	48	110	14	42,5	348	259	360	687/725	250	300	350	19	5
T3C 200L		6312		200	318	305	133	19	55	110	16	49	388	297	399	768	300	350	400	19	5
T3C 225S	4,8	6313		225	356	286	149	19	60	140	18	53	436	328	465	814	350	400	450	19	5
T3C 225M	2			225	356	311	149	19	55	110	16	49	436	328	465	809	350	400	450	19	5
	4,6,8			225	356	311	149	19	60	140	18	53	436	328	465	839	350	400	450	19	5
T3C 250M	2	6314		250	406	349	168	24	60	140	18	53	484	366	506	918	400	500	550	19	5
	4,6,8			250	406	349	168	24	65	140	18	58	484	366	506	918	400	500	550	19	5
T3C 280S/M	2	6316		280	457	368/419	190	24	65	140	18	58	557	388	559	984/1035	400	500	550	19	5
	4,6,8			280	457	368/419	190	24	75	140	20	67,5	557	388	559	984/1035	400	500	550	19	5
T3C 315S	2	6314		315	508	406	216	28	65	140	18	58	630	525	680	1160	550	600	660	24	6
	4,6,8	NU319	6319	315	508	406	216	28	80	170	22	71	630	525	680	1190	550	600	660	24	6
T3C 315M/L	2	6314		315	508	457/508	216	28	65	140	18	58	630	525	680	1310	550	600	660	24	6
	4,6,8	NU319	6319	315	508	457/508	216	28	80	170	22	71	630	525	680	1340	550	600	660	24	6
T3C 355M/L	2	6319		355	610	560/630	254	28	75	140	20	67,5	740	565	820	1770	680	740	800	24	6
	4,6,8	NU322	6322	355	610	560/630	254	28	95	170	25	86	740	565	820	1840	680	740	800	24	6

